

OSHA HazCom Standard 29 CFR 1910,1200(g) and GHS Rev 03.

Issue date 06/11/2015

Reviewed on 06/11/2015

Millerinitesion

· Product identifier

- Conney Item# 606041
- · Trade name: Precision Calibration Gas Mixture
- · Product number: G-1315
- Relevant identified uses of the substance or mixture and uses advised against Used for calibration of gas measuring devices. Not suitable for human consumption.
- · Product description

Calibration gas mixture consisting of Carbon Monoxide, Hydrogen Sulfide, Methane, Oxygen and Nitrogen.

- · Application of the substance / the mixture Pressurized gas, requires appropriate regulator to dispense.
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
 Gasco Affiliates, LLC
 320 Scarlett Blvd.
 Oldsmar, Fl 34677

TELEPHONE NUMBER: (800) 910-0051

FAX NUMBER: (866) 755-8920 E-MAIL: info@gascogas.com Emergency telephone number:

Inside the US: 1-800-424-9300 (CHEMTREC, 24 hours)
Outside the US: 1-703-527-3887 (CHEMTREC, 24 hours)

2 Fezera(s) (demii/leation

· Classification of the substance or mixture



GHS04 Gas cylinder

Press Gas

H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Repr. 1A

H360 May damage fertility or the unborn child.



Acute Tox. 4

H332 Harmful if inhaled.

Simple Asphyxiant

May displace oxygen and cause rapid suffocation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





OSHA HazCom Standard 29 CFR 1910.1200(a) and GHS Rev 03.

Issue date 06/11/2015

Reviewed on 06/11/2015

Trade name: Precision Calibration Gas Mixture

- · Signal word Danger
- · Hazard-determining components of labeling:

Carbon Monoxide

· Hazard statements

Contains gas under pressure; may explode if heated.

Harmful if inhaled.

May damage fertility or the unborn child.

May displace oxygen and cause rapid suffocation.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

Store locked up.

Protect from sunlight. Store in a well-ventilated place.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Unknown acute toxicity:

99.5 percent of the mixture consists of ingredient(s) of unknown toxicity.

- Classification system:
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 1 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0Fire = 1

REACTIVITY 0 Reactivity = 0

· Hazard(s) not otherwise classified (HNOC): None known

<u>ទី៩២៣០ទៅលោវ៣០ខ្មែរក្រើបាលលើ</u>បានប្រទាំង

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous Compone	ents:	,
CAS: 7727-37-9 RTECS: QW 9700000	Nitrogen ♦ Press. Gas, H280; Simple Asphyxiant	75.470 - 91.799%
CAS: 7782-44-7	Oxygen ② Oxid. Gas 1, H270; ◇ Press. Gas, H280	8 - 21%
CAS: 74-82-8 RTECS: PA 1490000	Methane ♠ Flam. Gas 1, H220; Press. Gas, H280	0.1 - 3.0%
<u> </u>	I To the state of	// and an area 3\

(Contd. on page 3)

OSHA HazCom Standard 29 CFR 1910.1200(a) and GHS Rev 03.

Issue date 06/11/2015

Reviewed on 06/11/2015

Trade name: Precision Calibration Gas Mixture

CAS: 630-08-0 RTECS: FG 3500000	Carbon Monoxide � Flam. Gas 1, H220; � Acute Tox. 3, H331; � Repr. 1A, H360; STOT RE 1, H372; Press. Gas, H280	0.0005 - 0.51%
CAS: 7783-06-4	Hydrogen Sulfide https://doi.org/10.16/49/20 ; ♦ Acute Tox. 2, H330; ♦ Aquatic Acute 1, H400; Press. Gas, H280	0.0005 - 0.02%

William Chierine

· Description of first aid measures

After inhalation:

Generally the product does not irritate with inhalation.

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.

In case of unconsciousness, place patient securely on side position for transportation.

· After skin contact:

Generally the product does not irritate the skin.

In cases of contact with liquified material, frostbite may occur. Immerse frostbite in cool-warm water and seek medical attention.

· After eye contact:

Not anticipated under normal use.

If irritation occurs thoroughly wash the exposed area and discontinue use. Seek medical attention if any adverse effect occurs.

- · After swallowing: Not a normal route of entry.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed.
 No further relevant information available.

No futtier relevant information availa

* ស៊ីដូខ្មែរប្រែប្រែប្រជាទេវិទីបទេ

· Extinguishing media

· Suitable extinguishing agents:

Use fire fighting measures that suit the environment.

Use water spray to cool fire-exposed containers.

· Special hazards arising from the substance or mixture

Closed containers may explode when exposed to extreme heat.

If incinerated, product will release the following toxic fumes: Oxides of Carbon, Nitrogen (NOx) and Sulfur.

· Advice for firefighters

This gas mixture is not flammable; however, containers, when involved in fire, may rupture or burst in the heat of the fire. Firefighters should be aware of the presence of Hydrogen Sulfide in this gas mixture, which can cause significant health effects.

Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

COACONGIUNG WALESCAMPAGUIAS DE

- Personal precautions, protective equipment and emergency procedures In a confined area, NIOSH approved respiratory protection may be required. Treat any fumes as toxic.
- · Environmental precautions: Inform authorities in case of gas release.
- · Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

(Contd. on page 4)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/2015

Reviewed on 06/11/2015

Trade name: Precision Calibration Gas Mixture

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

' 74 Ferrolling state starting

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Be aware of any signs of dizziness or fatigue; exposures to fatal concentrations of this gas mixture could occur without any significant warning symptoms due to the potential for oxygen deficiency (simple asphyxiation). Do not attempt to adjust, repain or in any other way modify the cylinders containing this gas mixture. If there is a malfunction or another type of operational problem, contact nearest distributor immediately.

· Information about protection against explosions and fires:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Keep protective respiratory device available.

Do not cut, grind or weld on container that contains or contained product.

Do not spray on a naked flame or any incandescent material.

· Conditions for safe storage, including any incompatibilities

Store away from strong oxidizing agents, strong bases, phosphorous, organic materials and powdered metals.

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool location.

Cyliners should be firmly secured to prevent falling or being knocked over. Cylinders must be protected from the environment, and preferably kept at room temperature. Cylinders should be stored in dry, well-ventilated areas, away from sources of heat, ignition, and direct sunlight. Protect cylinders against physical damage. Full and empty cylinders should be segregated. Use a "first-in, first-out" inventory system to prevent full containers freom being stored for long periods of time.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · Specific end use(s) No further relevant information available.

His Exposition control special major protection in

· Additional information about design of technical systems: No further data; see section 7.

Control parameters

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

· Components with occupational exposure limits:

7727-37-9 Nitrogen

TLV withdrawn TLV, see App. F; simple asphyxiant

74-82-8 Methane

TLV refer to Appendix F, 1000ppm

(Contd. on page 5)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/2015

Reviewed on 06/11/2015

Trade name: Precision Calibration Gas Mixture

08-0 Carbon Monoxide
Long-term value: 55 mg/m³, 50 ppm
Long-term value: 40 mg/m³, 35 ppm Ceiling limit value: 229 mg/m³, 200 ppm
Long-term value: 29 mg/m³, 25 ppm BEI
3-06-4 Hydrogen Sulfide
Ceiling limit value: 20; 50* ppm *10-min peak; once per 8-hr shift
Ceiling limit value: 15* mg/m³, 10* ppm *10-min
Short-term value: 7 mg/m³, 5 ppm Long-term value: 1.4 mg/m³, 1 ppm
edients with biological limit values:
08-0 Carbon Monoxide
3.5 % of hemoglobin blood end of shift
Carboxyhemoglobin (background, nonspecific)
20 ppm end-exhaled air end of shift Carbon monoxide (background, nonspecific)

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Breathing equipment:

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

- · Protection of hands: Not required.
- · Eye protection: Not necessary under normal conditions.

នៅឱ្យស្នាន់នៅនៅលើការ៉ាម៉ាស្រីស្រីស្រីស្រីស្រីស្រី

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:

Gaseous

Color:

Clear, colorless

· Odor:

Mild

· Odor threshold:

Not determined.

· pH-value:

Not determined.

(Contd. on page 6)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Trade name: Precision Calibration Gas Mixture

Reviewed on 06/11/2015

· Change in condition

Issue date 06/11/2015

Melting point/Melting range: Boiling point/Boiling range: Not determined. -195 °C (-319 °F)

· Flash point:

Not applicable.

· Flammability (solid, gaseous):

Not determined.

· Ignition temperature:

Decomposition temperature:

Not determined.

· Auto igniting:

Product is not self-igniting.

· Danger of explosion:

Not determined.

· Explosion limits:

Lower: Upper: Not determined. Not determined.

· Vapor pressure:

Not determined.

· Density @ 20 °C (68 °F):

0.023 g/cm3 (0.192 lbs/gal)

· Relative density

Not determined. Not determined.

· Vapor density · Evaporation rate

Not applicable.

· Solubility in / Miscibility with

Water:

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Kinematic: Not determined. Not determined.

· Solvent content:

Organic solvents:

0.0 %

Other information

No further relevant information available.

* 100 Selolliyaenioneeminiya

- · Reactivity Stable under normal conditions
- · Chemical stability Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Heat, flame and ignition sources.
- · Incompatible materials:

Strong oxidizing agents, strong bases, phosphorous, organic materials and powdered metals.

· Hazardous decomposition products: Oxides of Carbon, Nitrogen (NOx) and Sulfur.

* Katio Xino logica di internationa

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values	thai	t are re	levant i	for c	lassification:
------------------	------	----------	----------	-------	----------------

630-08-0 Carbon Monoxide

Inhalative LC50/4 h

7520 mg/l (rat)

(Contd. on page 7)

OSHA HazCom Standard 29 CFR 1910.1200(a) and GHS Rev 03.

Issue date 06/11/2015

Reviewed on 06/11/2015

Trade name: Precision Calibration Gas Mixture

7783-06-4	7783-06-4 Hydrogen Sulfide				
Inhalative	LC50/4 h	634 mg/l (mouse)			
		444 mg/l (rat)			
	LC50/96 hours	0.016 mg/l (Pimephales)			
74-82-8 M	ethane				
Inhalative	LC50/4 h	217 mg/l (mouse)			

- · Primary irritant effect:
- · on the skin: No irritating effect.
- · on the eye: No irritating effect.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)
- Group 1 Carcinogenic to humans
- Group 2A Probably carcinogenic to humans
- Group 2B Possibly carcinogenic to humans
- Group 3 Not classifiable as to its carcinogenicity to humans
- Group 4 Probably not carcinogenic to humans

None of the ingredients are listed. • NTP (National Toxicology Program) None of the ingredients are listed. • OSHA-Ca (Occupational Safety & Health Administration)

* 12Eaglogicalimiotamailom

- · Toxicity The hazards for the aquatic environment are unknown.
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:

None of the ingredients are listed.

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Generally not hazardous for water.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

* [Kalifigeralaegierigerilleriller

- · Waste treatment methods
- · Recommendation:

Release all residual gas pressure in a well ventilated area. Verify the cylinder is completely empty (0 PSIG). Remove or cover any hazard labels. Return empty supplier for recycling.

NOTE: Check with the local waste authority before placing any gas cylinder into a waste container for pickup. GASCO encourages the consumer to return all cylinders.

· Waste disposal key: The U.S. EPA has not published waste numbers for this product's components.

(Contd. on page 8)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/2015

Reviewed on 06/11/2015

Trade name: Precision Calibration Gas Mixture

- · Uncleaned packagings:
- · Recommendation: Return cylinder and unused product to supplier.

· UN-Number

· DOT, ADR, IMDG, IATA

UN1956

· UN proper shipping name

· DOT

Compressed gas, n.o.s.

· ADR · IMDG, IATA UN1956 Compressed gas, n.o.s. COMPRESSED GAS, N.O.S.

· Transport hazard class(es)

· DOT



· Class

2.2

Label

2.2

· ADR



· Class

2.2 1A

Label

2.2

· IMDG, IATA



· Class

2.2

· Label

2.2

· Packing group

· Environmental hazards:

Not applicable. Not applicable.

· Special precautions for user Danger code (Kemler):

20

· EMS Number:

F-C,S-V

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

Not applicable.

· Transport/Additional information:

· DOT

· Quantity limitations

On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg

· ADR

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 9)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/2015

Reviewed on 06/11/2015

Trade name: Precision Calibration Gas Mixture

· UN "Model Regulation":

UN1956, Compressed gas, n.o.s., 2.2

* [[5][Regillerionvarritoraneritora

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara
- · Section 355 (extremely hazardous substances):

7783-06-4 Hydrogen Sulfide

· Section 313 (Specific toxic chemical listings):

7783-06-4 Hydrogen Sulfide

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · California Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

630-08-0 Carbon Monoxide

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

7783-06-4 Hydrogen Sulfide

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS04 GHS07 GI

- · Signal word Danger
- · Hazard-determining components of labeling:

Carbon Monoxide

· Hazard statements

Contains gas under pressure; may explode if heated.

Harmful if inhaled.

May damage fertility or the unborn child.

May displace oxygen and cause rapid suffocation.

(Contd. on page 10)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/2015

Reviewed on 06/11/2015

Trade name: Precision Calibration Gas Mixture

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

Store locked up.

Protect from sunlight. Store in a well-ventilated place.

Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

Nitrogen	75.470 - 91.799%
Press. Gas, H280; Simple Asphyxiant	
Oxygen	8 - 21%
♠ Oxid. Gas 1, H270; ♦ Press. Gas, H280	
Methane	0.1 - 3.0%
♦ Flam. Gas 1, H220; Press. Gas, H280	
Carbon Monoxide	0.0005 - 0.51%
♠ Flam. Gas 1, H220; ♠ Acute Tox. 3, H331; ♠ Repr. 1A, H360; ŠTOT RE 1, H372; Press. Gas, H280	
Hydrogen Sulfide	0.0005 - 0.02%
♦ Flam. Gas 1, H220; ♦ Acute Tox. 2, H330; ♦ Aquatic Acute 1, H400; Press. Gas, H280	
	Oxygen Oxygen Oxid. Gas 1, H270; Press. Gas, H280 Methane Flam. Gas 1, H220; Press. Gas, H280 Carbon Monoxide Flam. Gas 1, H220; Acute Tox. 3, H331; Repr. 1A, H360; STOT RE 1, H372; Press. Gas, H280 Hydrogen Sulfide Flam. Gas 1, H220; Acute Tox. 2, H330; Aquatic Acute 1,

[·] Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

* Millionne internation

· Relevant phrases

Gasco Affiliates, LLC, makes no express or implied warranties, guarantees or representations regarding the product or the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Gasco Affiliates, LLC shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use or reliance upon the information herein.

· Date of preparation / last revision 06/11/2015 / -

· Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Safety Data Sheet (SDS)
OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/2015

Reviewed on 06/11/2015

Trade name: Precision Calibration Gas Mixture

Flam. Gas 1: Flammable gases, Hazard Category 1 Oxid. Gas 1: Oxidising Gases, Hazard Category 1 Oxid. Gas 1: Oxidising Gases, Hazard Category 1
Press. Gas: Gases under pressure: Compressed gas
Acute Tox. 2: Acute toxicity, Hazard Category 2
Acute Tox. 3: Acute toxicity, Hazard Category 3
Acute Tox. 4: Acute toxicity, Hazard Category 4
Repr. 1A: Reproductive toxicity, Hazard Category 1A
STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1
** Data compared to the provious version altered

* Data compared to the previous version altered.
SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106